

PHOENIX


Mansiri Trading



Bitumen Sprayer

FOR
QUALITY ROAD
CONSTRUCTION

Bitumen Sprayer Bitumen Pump 2" x 2" Size positive displacement gear pump with output 350 Liters / Min. (Max). Air Compressor Make - ELGI 2 CYL, 3 H.P. working pressure 9 kg. / cm 2 13.25m3 Capacity 360 LPM. 550 R.P.M. Driving Unit Krilosker / HTC Vertical air Cooled diesel engine. Bitumen Spraying Pressure 0 to 6 Kg. / cm 2 Operator Platform Technometer: Slow Speed 0.5 Meter / Min.

PRODUCT SPECIFICATION

Model	BD - 3000	BD - 4000	BD - 6000	BD - 7000
Length	2100 mm	2400 mm	3100 mm	3300 mm
Width	1800 mm	1800 mm	1900 mm	1900 mm
Height	1500 mm	1500 mm	1550 mm	1650 mm
Capacity	3000 Ltrs	4000 Ltrs	6000 Ltrs	7000 Ltrs
Man Holer	600 mm	600 mm	600 mm	600 mm
Insulation	50 mm	50 mm	50 mm	50 mm
Fuel Consumption of Burner	20 Ltrs. / Hr.	20 Ltrs. / Hr.	20 Ltrs. / Hr.	20 Ltrs. / Hr.
Burner	Compressed Air Type			
Burner Fuel Tank	50 Ltrs			
Mounting	Ashok Leyland or Tata			
Tank Shape	Ovel Shape			

- **Bitumen Pump**

2" x 2" Size positive displacement gear pump with output 350 Liters / Min. (Max).

- **Air Compressor**

Make - ELGI 2 CYL, 3 H.P. working pressure 9 kg. / cm² 13.25m³ Capacity 360 LPM. 550 R.P.M.

- **Driving Unit**

Krilosker / HTC Vertical air Cooled diesel engine.

- **Bitumen Spraying Pressure**

0 to 6 Kg. / cm²

- **Operator Platform**

Technometer: Slow Speed 0.5 Meter / Min.

- **Temperature Gauge**

0 - 250°C at front of tank



Mansiri Trading Enterprises Pvt. Ltd.
Mahalaxmistan, Lalitpur

